

**Application No. 10/620,749****Attorney Docket No. 5701-01293****Amendment Dated 18 April 2005****Reply to Office Action dated 18 November 2005 & Advisory Action dated 14 March 2005****Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

Claims 1-6 have been cancelled without prejudice.

7. (original): A method of estimating a state of a target vehicle on a roadway, comprising::

- a. generating an estimate of a curvature of the roadway;
- b. estimating an unconstrained state and associated covariance thereof of the target vehicle;
- 5 c. establishing at least one prospective constraint of the target vehicle, wherein at least one prospective constraint is responsive to said estimate of the curvature of the roadway;
- d. estimating at least one constrained state and associated covariance thereof of the target vehicle corresponding to said at least one prospective constraint of the target vehicle;
- 10 e. determining a most likely state of the target vehicle, wherein said most likely state of the target vehicle is selected from said unconstrained state of the target vehicle and said at least one constrained state of the target vehicle; and
- 15 f. if said at least one constrained state of the target vehicle is the most likely state, then fusing the unconstrained state and covariance thereof of the target vehicle with the associated constrained state and covariance of said most likely state and outputting at least one of the fused state and the associated fused covariance thereof of the target as the estimated state or covariance of the target; otherwise outputting at least one of the unconstrained state and the associated unconstrained covariance thereof of the target as the estimated state or covariance of the target.

**Application No. 10/620,749****Attorney Docket No. 5701-01293****Amendment Dated 18 April 2005****Reply to Office Action dated 18 November 2005 & Advisory Action dated 14 March 2005**

8. (original): A method of estimating a state of a target vehicle on a roadway as recited in claim 7, wherein the operation of estimating the curvature of the roadway comprises:

a. generating a speed measurement by measuring a longitudinal speed of a host vehicle traveling on the roadway;

b. generating a yaw rate measurement by measuring or determining a yaw rate of said host vehicle; and

c. estimating at least one curvature parameter, wherein said at least one curvature parameter is representative of a curvature of the roadway, and the operation of estimating at least one curvature parameter is responsive to said speed measurement and is responsive to said yaw rate measurement.

9. (original): A method of estimating a state of a target vehicle on a roadway as recited in claim 8, wherein said at least one curvature parameter comprises at least one parameter of a clothoid model of curvature, and said Clothoid model of curvature is referenced to a coordinate system of said host vehicle.

10. (original): A method of estimating a state of a target vehicle on a roadway as recited in claim 9, wherein said at least one curvature parameter comprises first and second parameters of a clothoid model, wherein said first parameter is a constant, and said second parameter is a sensitivity of curvature to a distance along the roadway.

11. (original): A method of estimating a state of a target vehicle on a roadway as recited in claim 8, wherein the operation of estimating at least one curvature parameter comprises processing said measurements of speed and yaw rate with at least one Kalman filter.

12. (original): A method of estimating a state of a target vehicle on a roadway as recited in claim 11, wherein said at least one Kalman filter comprises first and second Kalman filters, said first Kalman filter is adapted to estimate a first set of state variables from said speed measurement and from said yaw rate measurement, and said second Kalman filter is adapted to estimate said at least one curvature parameter from said estimate of said first set of state variables.

**Application No. 10/620,749****Attorney Docket No. 5701-01293****Amendment Dated 18 April 2005****Reply to Office Action dated 18 November 2005 & Advisory Action dated 14 March 2005**

13. (original): A method of estimating a state of a target vehicle on a roadway as recited in claim 12, wherein said first set of state variables comprises vehicle velocity, vehicle acceleration, vehicle yaw rate and vehicle yaw acceleration.
14. (original): A method of estimating a state of a target vehicle on a roadway as recited in claim 7, wherein the operation of estimating an unconstrained state and associated covariance of the target vehicle comprise:
- a. measuring a range, a range rate and an azimuth of the target vehicle relative to a host vehicle; and
  - b. estimating said unconstrained state of the target vehicle from said measurements of the range, range rate and azimuth of the target vehicle relative to the host vehicle.
15. (original): A method of estimating a state of a target vehicle on a roadway as recited in claim 7, further comprising the operation of transforming said unconstrained state of the target vehicle to a coordinate system corresponding to said estimate of the curvature of the roadway.
16. (original): A method of estimating a state of a target vehicle on a roadway as recited in claim 7, wherein said at least one prospective constraint of the target vehicle is applied to a lateral position of the target vehicle, and a longitudinal position of the target vehicle is unconstrained.
17. (original): A method of estimating a state of a target vehicle on a roadway as recited in claim 7, wherein said at least one prospective constraint of the target vehicle comprises a plurality of prospective constraints, and at least two different prospective constraints correspond to different lanes of the roadway.

**Application No. 10/620,749****Attorney Docket No. 5701-01293****Amendment Dated 18 April 2005****Reply to Office Action dated 18 November 2005 & Advisory Action dated 14 March 2005**

18. (original): A method of estimating a state of a target vehicle on a roadway as recited in claim 7, wherein the operation of determining the most likely state of the target vehicle comprises:

- a. determining at least one likelihood value, wherein said at least one likelihood value corresponds to said at least one prospective constraint of the target vehicle being active and said at least one likelihood value is responsive to a corresponding at least one distribution function evaluated at a value corresponding to said unconstrained state of the target vehicle;
- b. determining a probability of a first constrained state of the target vehicle, wherein said probability is responsive to said at least one likelihood value;
- c. testing at least one hypothesis that said unconstrained state of the target vehicle corresponds to said first constrained state, and
- d. identifying a most likely state of the target vehicle responsive to the operation of testing said at least one hypothesis.

19. (original): A method of estimating a state of a target vehicle on a roadway as recited in claim 18, wherein the operation of determining the most likely state of the target vehicle comprises establishing at least one a priori probability of a transition from a first state to a second state of the target vehicle, wherein said first and second states can be either the same or different states, and said probability of said first constrained state of the target vehicle is responsive to said at least one a priori probability.

20. (original): A method of estimating a state of a target vehicle on a roadway as recited in claim 18, wherein said at least one distribution function is responsive to said covariance of the particular constrained state of the target vehicle.

21. (original): A method of estimating a state of a target vehicle on a roadway as recited in claim 18, wherein said at least one constrained state comprises a plurality of constrained states, and said first constrained state comprises a combination of said plurality of constrained states.

**Application No. 10/620,749****Attorney Docket No. 5701-01293****Amendment Dated 18 April 2005****Reply to Office Action dated 18 November 2005 & Advisory Action dated 14 March 2005**

22. (original): A method of estimating a state of a target vehicle on a roadway as recited in claim 18, wherein said first constrained state comprises a most likely of said at least one constrained state of the target vehicle.
23. (original): A method of estimating a state of a target vehicle on a roadway as recited in claim 18, wherein said first constrained state comprises one of said at least one constrained state of the target vehicle.
24. (original): A method of estimating a state of a target vehicle on a roadway as recited in claim 18, wherein the operation of testing at least one hypothesis is responsive to the most recent estimates of said state of the target vehicle.
25. (original): A method of estimating a state of a target vehicle on a roadway as recited in claim 18, wherein the operation of testing at least one hypothesis comprises identifying a particular constrained state of the target vehicle corresponding to a most likely of said at least one constrained state of the target vehicle, calculating a value of a function responsive to a difference between said unconstrained state and said particular constrained state, and comparing said value of said function with a threshold, whereby said hypothesis is satisfied if said value of said function is less than said threshold.
26. (original): A method of estimating a state of a target vehicle on a roadway as recited in claim 25, wherein said threshold is responsive to the particular constraint associated with said particular constrained state of the target vehicle.
27. (original): A method of estimating a state of a target vehicle on a roadway as recited in claim 26, wherein said threshold is relatively lower for said particular constrained state corresponding to an increased threat by the target vehicle to host vehicle.
28. (original): A method of estimating a state of a target vehicle on a roadway as recited in claim 27, wherein said particular constrained state corresponding to an increased threat by the target vehicle to the host vehicle is selected from the target vehicle moving in the same lane as the host vehicle, and the target vehicle changing lanes to said same lane as the host vehicle.

Claims 29-37 have been cancelled without prejudice.

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

☐ **BLACK BORDERS**

☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**

☐ **FADED TEXT OR DRAWING**

☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**

☐ **SKEWED/SLANTED IMAGES**

☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**

☐ **GRAY SCALE DOCUMENTS**

☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**

☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**

☐ **OTHER:** \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**